



## WHY ACC

- ü ACC offers products from the **top-class** activated carbon manufacturers.
- ü ACC ensures a **one-stop service** for varies demands from customers.
- ü **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- ü Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

## ACC Carrier Series for Gas Purification

It is produced by selected coal materials and is mainly used for treatment of poisonous smelly industrial waster gas, including hydrogen sulfide, methyl mercaptan, sulfur dioxide, dimethyl sulfide, two methyl sulfide, mercury vapor, ammonia, etc.

### Features & Benefits

- I High adsorption capacity
- I High activity

Item No.	Specification						
	Moisture (%)	Hardness (%)	CTC (%)	Apparent Density (g/l)	H2S Breakthrough Ability (%)	Size (mm)	Remarks
TZK14B	≤15	≥95	60-70	≤680	≥0.14	Customer made	
TZNa14B	≤15	≥95	60-70	≤660	≥0.14	Customer made	
TPK14B	≤15	≥95	≥60	≤580	≥0.14	3.6-4.1	
TPN14B	≤15	≥95	≥60	≤580	≥0.14	3.6-4.1	
TZI14B	≤15	≥95	60-70	≤670	≥0.14	Customer made	
TZSB	≤5	≥95	60-70	≤620	----	Customer made	Removing mercury vapor
TPSB	≤5	≥95	≥60	≤540	----	3.6-4.1	
TZCuB	≤5	≥95	50-60	≤580	----	Customer made	Removing acidic odor
TZHSB	≤15	≥95	≥60	≤630	---	4.0±0.2	Removing Alkaline Odor represented by Ammonia
TZP	≤15	≥95	60-70	≤710	---	Customer made	
TPP	≤15	-----	≥60	----	---	----	

**Package:** Packed in 500 or 600kg jumbo bag. Other packaging is available upon your request.

**Standards:** All the above test methods are performed using ASTM protocol for activated carbon.

### Xiamen All Carbon Corporation

TEL: +86 592 2278129 FAX: +86 592 2278123

E-MAIL: [info@allcarbon.com.cn](mailto:info@allcarbon.com.cn) [Http://www.allcarbon.com.cn](http://www.allcarbon.com.cn)

Add: Unit F-G, 10/F, Zhenhaoge Building, Guomao Golden Coast, No.99 Lujiang Road, Xiamen China, 361001