



ACC Gaspur for Gas Purification

WHY ACC

- ü ACC offers products from the **top-class** activated carbon manufacturers.
- ü ACC ensures a **one-stop service** for varies demands from customers.
- ü **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- ü Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

It is widely used for treatment of bad smell like hydrogen sulfide, volatile organic compounds and acid gas (such as HCl, SO) in sewage treatment plant, smelting plant, paper mill and sewer.

Features & Benefits

- I High H₂S breakthrough ability
- I High Hardness
- I Good pore structure

Item No.	Specification					
	GP HiCOR	Moisture (%)	Hardness (%)	H ₂ S Breakthrough Ability (g/cc)	Apparent Density (g/l)	Size (mm)
05B		≤15	≥95	≥0.05	570±30	3.5-4.0
10B		≤15	≥95	≥0.10	570±30	3.5-4.0
15B		≤15	≥95	≥0.15	550±30	3.5-4.0
20B		≤15	≥94	≥0.20	510±30	3.5-4.0
25B		≤15	≥93	≥0.25	470±30	3.5-4.0
30B		≤15	≥90	≥0.30	420±30	3.5-4.0

Other specification can be provided upon the customer's requirements.

Package: Packed in 500kg jumbo bag. Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.