



WHY ACC

- ü ACC offers products from the **top-class** activated carbon manufacturers.
- ü ACC ensures a **one-stop service** for varies demands from customers.
- ü **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- ü Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

ACC Gaspur for Gas Purification

It is widely used for purification of chemical raw materials gas, chemical synthetic gas, pharmaceutical industrial gas, carbon dioxide gas used in beverage and hydrogen, nitrogen hydrogen chloride, ethylene, ethane, cracking gas, inert gas and purification, separation and refinement of atomic facilities exhaust.

Features & Benefits

- I High hardness
- I Low ash content

Item No.	Specification						
	GP ZK	Moisture (%)	Hardness (%)	Ash (%)	CTC (%)	Apparent Density (g/l)	Size (mm)
2050B		≤3	≥95	≤8	≥50	540±20	2.0±0.2
2060B		≤3	≥95	≤12	≥60	510±20	2.0±0.2
2070B		≤3	≥95	≤12	≥70	480±20	2.0±0.2
3050B		≤3	≥95	≤8	≥50	530±20	3.0±0.2
3060B		≤3	≥95	≤12	≥60	500±20	3.0±0.2
3070B		≤3	≥95	≤12	≥70	470±20	3.0±0.2
4050B		≤3	≥95	≤8	≥50	530±20	4.0±0.2
4060B		≤3	≥95	≤12	≥60	490±20	4.0±0.2
4070B		≤3	≥95	≤12	≥70	470±20	4.0±0.2
5060B		≤3	≥95	≤12	≥60	490±20	5.0±0.2
7060B		≤3	≥95	≤12	≥60	480±20	7.0±0.2

Package: Packed in 500kg jumbo bag. Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.