



WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for various demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

ACC DS 4060 G

This product is a coal-based pellet carbon designed for the removal of acid gases and odor compounds from air. It is manufactured by high-temperature steam activation followed by chemical impregnation.

DS 4060 G series is proved to be well-performed in many odor control applications, including industrial processes, municipal treatment plants, paper plants, and indoor air filtration.

It provides very high capacities for compounds that are not strongly adsorbed by standard carbon, including hydrogen sulfide (H₂S), mercaptans, sulfur dioxide, chlorine, and hydrogen chloride.

Package: Packed in 500kg jumbo bag. Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.

SPECIFICATIONS

DS 4060 G

CCl ₄ by weight	60% min
Moisture by weight	15% max
Mean Particle Diameter	4 mm
H ₂ S Breakthrough Capacity	0.14 g/cc min
Ash Content by weight	12%
Ball Pan Hardness	95% min