



ACC GP 410/830 G

WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for varies demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- ✓ Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

This product is a granular activated carbon used in the purification of re-circulating amine streams, in glycol dehydration units and gas purification units where amines are used for sour gas treatment.

The raw material is reagglomerated metallurgical grade bituminous coal, which is featured by uniformly activated granules, high pore volume and faster adsorption.

Package: Packed in 500kg jumbo bag. Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.

SPECIFICATIONS

GP 410G

Butane activity	23.3% min
Moisture (as packaged)	2% max
Particle Size	4*10
4 US Mesh (4.75mm)	6% max
< 10 US Mesh (2.00mm)	3% max

GP 830G

Iodine number	900mg/g min
Ash content	10% max
Moisture (as packaged)	2% max
8 US Mesh (2.36mm)	15% max
< 30 US Mesh (0.60mm)	4% max