



## ACC AC 3080 G

### WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for varies demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- ✓ Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

ACC 3080G is a high activity virgin pelletized activated carbon designed for gas phase applications. It is an extruded coal based product activated by high temperature under rigidly controlled conditions.

The 3mm pellet diameter does reduce the bed depth due to more rapid adsorption. It offers effective VOC and hydrocarbon emission control and exceptional performance and economics when treating contaminant concentrations in excess of 2,000 ppmv.

Some of the typical applications include: catalyst support, gas processing, industrial processes, VOC industrial, air purification, etc.

**Package:** Packed in 500kg jumbo bag. Other packaging is available upon your request.

**Standards:** All the above test methods are performed using ASTM protocol for activated carbon.

### SPECIFICATIONS

#### AC 3080 G

Carbon Tetrachloride	80% min
Moisture (as packaged)	4% max
Hardness Number	93% min
Ash Content	14% min
Particle Size	3 mm
8 US Mesh (2.36mm)	95% min
< 8 US mesh (2.36mm)	5% max