



ACC WS 830 i900 G-2

WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for various demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

It is a granular activated carbon developed for the removal of dissolved organic compounds from water and wastewater as well as industrial and food processing streams. It can be used in a variety of liquid phase applications.

This product is manufactured from select grades of bituminous coal through a process known as reagglomeration to produce a durable granular product capable of withstanding the abrasion associated with repeated backwashing, air scouring, hydraulic transport, and reactivation for reuse.

Package: Packed in 500kg jumbo bag. Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.

SPECIFICATIONS	
WS 830 i900 G-2	
Specifications	
Bedline Number	900mg/g min
Moisture by weight	2% max
Effective Size	0.8-1.0 mm
Uniformity Coefficient	2.1 max
Abrasion Number	78% min
Screen Size by weight, US Sieve Series	
On 8 Mesh	15% max
Through 30 mesh	4% max
Typical Properties	
Apparent Density	0.56g/cc min
Water Extractable	< 1%
Non-Wettable	< 1%