



## ACC GP 325 G i400/500/600

### WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for various demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.  
Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

This product is a powdered activated carbon impregnated with proprietary ingredients to enhance mercury capture in flue gas treatment applications.

It is specially designed to enhance mercury capture in flue gas streams. This product is injected directly into the flue gas stream and is easily removed by existing particulate control devices. It can be landfilled with the ash as a non-hazardous material.

This series is proved to be particularly effective for utilities burning Powder River Basin (PRB) coals. It can also be well-performed in following applications: coal-fired power plants, cement kilns, industrial boilers, municipal waste combustors, hazardous waste combustors, hospital waste incinerators.etc.

**Package:** Packed in 500kg jumbo bag. Other packaging is available upon your request.

**Standards:** All the above test methods are performed using ASTM protocol for activated carbon.

### SPECIFICATIONS

#### GP 325 G i400/500/600

#### Specifications

Moisture  
(as packed by weight) 8% max

Screen Size by weight, U.S Sieve Series

<100 US Mesh 100% min

< 325 US Mesh 95% min

#### Typical Properties

Iodine number 400-600 mg/g

Apparent Density (tamped) 0.4-0.8 g/cc

Ignition Temperature > 350°C