

ACC GP 325 G-12

WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for various demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

This product is a high-performance brominated powdered activated carbon which is specially formulated to enhance mercury capture in fule gas treatment applicaitons, such as flue gas streams with elevated levels of SO₃.

It is specially designed to enhance mercury capture in flue gas streams. This product is injected directly into the flue gas stream and is easily removed by existing particulate control devices. The reduced ratio of carbon to fly ash and the product's inherent concrete friendliness preserves the fly ash suitability for sale or non-hazardous disposal.

This series is proved to be particularly effective in applications where there are elevated sulfur trioxide (SO₃) levels in the flue gas (such as coal-fired boilers burning high-sulfur coals).

Package: Packed in 500kg jumbo bag. Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.

SPECIFICATIONS

GP 325 G-12

Specifications

Moisture (as packed by weight)	12% max
Sieve Size by volume (laser analysis)	
<100 US Mesh	100% min
< 325 US Mesh	95% min

Typical Properties

Apparent Density (tamped)	0.4-0.8 g/cc
Ignition Temperature	> 350°C