

ACC GP 325 G-MC2

WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for various demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

This product is a powder activated carbon that is designed in flue gas treatment applications. Due to its surface area and pore volume, it is a very effective solution for removal of many flue gas contaminants.

Removal of this series is easily accomplished using existing particulate matter devices and can be landfilled with ash as non-hazardous material. In addition, this product has proved to be concrete-friendly, allowing some customers to continue or recapture the sale of activated carbon laden fly ash.

It can also be well-performed in following applications: coal-fired power plants, cement kilns, industrial boilers, municipal waste combustors, hazardous waste combustors, hospital waste incinerators, etc.

Package: Packed in 500kg jumbo bag. Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.

SPECIFICATIONS

GP 325 G-MC2

Specifications

Moisture (as packed by weight)	8% max
Screen Size by weight, U.S Sieve Series	
<100 US Mesh	100% min
< 325 US Mesh	99% min

Typical Properties

Apparent Density (tamped)	0.4-0.8 g/cc
Ignition Temperature	> 350 °C