



ACC GP 325 G-SPR

WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for various demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- ✓ Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

This product is a specially formulated non-brominated activated carbon that is designed to enhance mercury capture in fule gas treatment applicaitons.

It performs exceptionally well with boiler front end coal additives such as calcium bromide and has demonstrated greater than 50% reduction in mercury treatment costs when compared to standard products. It has also been shown to provide enhanced removal capability in baghouse applications.

It can also be well-performed in following applications: coal-fired power plants, cement kilns, industrial boilers, municipal waste combustors, hazardous waste combustors, hospital waste incinerators, etc.

Package: Packed in 500kg jumbo bag. Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.

SPECIFICATIONS

GP 325 G-SPR

Specifications

Moisture (as packed by weight)	12% max
Sieve Size by volume (laser analysis)	
<100 US Mesh	100% min
< 325 US Mesh	95% min
Typical Properties	
Apparent Density (tamped)	0.4-0.8 g/cc
Ignition Temperature	> 350°C