



ACC D9 Series for Waste Gas Treatment

WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for varies demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- ✓ Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

This product is specially designed for the industrial waste gas treatment, which contains hydrogen sulfide, methyl mercaptan, dimethyl sulfide, mercury vapor, ammonia gas.etc.

Features

- Good H₂S adsorption
- High Hardness

SPECIFICATIONS

	SAC-3070 C	SAC-3080 C	MD-4070 C	MD-4080C
Moisture (≤%)	5	5	5	5
Hardness (≥%)	98	98	98	98
H ₂ S (≥g/cc)	0.15	0.15	0.15	0.15
TC (≥%)	70	80	70	80
Packing Density (g/l)	400±20	380±20	400±20	380±20
Particle Size (mm)	φ 3.0	φ 3.0	φ 4.0	φ 4.0

Package: Packed in 500kg jumbo bag.
Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.