



ACC WS for COD Removal

WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for varies demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- ✓ Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

This product is metallic catalyst which is made by catalytic wet oxidation. Featured by great catalytic performance and stability, it can be well used in high concentrated organic wastewater treatment. Say the removal of COD in dye wastewater, petrochemical industrial waste water, etc, with removal rate reaches 95-99%.

SPECIFICATIONS

	MJ-3090 C	MJ-40100 C	MJ-4090 C	MD-40100 C
Moisture (≤%)		5	5	5
Hardness (≥%)	98	95	98	95
Ash Content (≤%)	7	7	7	7
Iodine Number (≥%)	1000	1100	1000	1100
CTC (≥%)	90	100	90	100
Packing Density (g/l)	380±20	350±20	380±20	350±20
Particle Size (mm)	φ 3.0	φ 3.0	φ 4.0	φ 4.0

Package: Packed in 500kg jumbo bag.
Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.