



ACC WS OLC 1240 G

WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
 - ✓ ACC ensures a **one-stop service** for various demands from customers.
 - ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

This product is a coconut activated carbon for the removal of dissolved organic contaminants, include taste and odor compounds, organic color, total organic carbon (TOC) and industrial chemicals such as chlorinated solvents (TCE, PCE). The pore structure enables it to be used for adsorption of both high and low molecule weight impurities from waters and liquids. The carbon is especially effective for adsorbing trace organic compounds, such as vinyl chloride, methylene chloride, MTBE and THM's disinfection by-products.

It can be used in a variety of water, wastewater and process liquid applications for the removal of dissolved organic compounds. Has been used in applications such as process water purification, wastewater treatment and industrial chemical purification.

Package: Packed in big jumbo bags or 25kg bags. Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.

SPECIFICATIONS

WS OLC 1240 G

Iodine Number, mg/g	1050 min
Ash, wt%	4.0 max
Moisture (As packaged), wt%	5 max
Density (Apparent), g/cc	0.48 min
Hardness Number	95 min
12 US Mesh (1.70mm), wt%	5 max
< 40 US Mesh (0.425mm) (F.A.S.), wt%	4 max