



## ACC WS 1240 i900 G

### WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for varies demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- ✓ Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

This product is produced from bituminous coal, can be utilized in the liquid phase for the promotion of oxidation, reduction, decomposition, substitution, and elimination reactions.

Specific applications include chloramines and hydrogen sulfide removal from potable water.

**Package:** Packed in big jumbo bags or 25kg bags. Other packaging is available upon your request.

**Standards:** All the above test methods are performed using ASTM protocol for activated carbon.

SPECIFICATIONS	
WS 1240 i900 G	
Iodine Number, mg/g	900 min
Abrasion Number	75 min
PH (Extractable)	5--8
Moisture (As Packaged), wt%	3.0 max
NSF 42- Arsenic [As], ppb	10 max
NSF 42- Antimony [Sb], ppb	6 max
NSF 42- Aluminum [Al], ppb	200 max
Prop 65- Arsenic [As], ppb	5 max
Prop 65- Antimony [Sb], ppb	3 max
Prop 65- Aluminum [Al], ppb	200 max
12 US Mesh (1.70mm), wt%	5 max
<40 US Mesh (0.425mm) (PAN), wt%	4 max