



ACC EVAP P12 H

WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
 - ✓ ACC ensures a **one-stop service** for various demands from customers.
 - ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

ACC Autocarb is used in the fuel tank to adsorb the hydrocarbon molecules in the pores and on the surface of the activated carbon, preventing hydrocarbon emissions into the environment. It has passed the test certificates from the world's major car manufacturers and carbon canister manufacturers. It accords with the emission control requirements of China VI Emission Standard and Euro VI Emission Standard.

Package: Packed in 320kg bags or 20kg bags. Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.

SPECIFICATIONS

EVAP P12 H

BWC	12 g/100ml
Moisture	2 mass-%
Apparent density	330 kg/m3
Hardness	75%
Pressure drop	3.2 KPa/m
PH	7.0
Ash (< 0.5mm)	0.01 mass-%
Size > 2mm	96 mass-%
Gasoline working ability (after 75 cycles)	7.2 g/100ml
Gasoline working ability (after 250 cycles)	6.5 g/100ml