



WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for varies demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- ✓ Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

ACC DS/MZ Series for H₂S Adsorption

To be applied in the fields of Impregnated Activated Carbon and other smell gas controlled AC. The existence of CO₂ doesn't affect the Activated carbon performance to H₂S and other acidic gases. With Size 4mm, it guarantees the airstream faces less pressure loss when in adsorbent equipments. Meanwhile, higher Hardness decreases the powder when Activated carbon is in application. The main application domains: smell gas control, sewage treatment, tannery, pulp mill and paper mill, acidic gases, such as HCL, SO₂ and volatile organic compounds.

Item No.	Specification					
DS	Moisture (%)	Hardness (%)	CTC (%)	H ₂ S(g/cc)	Apparent Density (g/l)	Size (mm)
MZ-10 C	15 max	95 min	65 min	0.1 min	450±20	3.5-4.0
MZ-15 C	15 max	95 min	70 min	0.15 min	450±20	3.5-4.0
MZ-20 C	15 max	90 min	75 min	0.2 min	450±20	3.5-4.0
MZ-30 C	15 max	90 min	85 min	0.3 min	450±20	3.5-4.0

Package: Packed in 500kg bags. Other packaging is available upon your request.

Standards: All the above test methods are performed using ASTM protocol for activated carbon.