



## ACC GP Granular Series for VOCS Treatment

### WHY ACC

- ✓ ACC offers products from the **top-class** activated carbon manufacturers.
- ✓ ACC ensures a **one-stop service** for varies demands from customers.
- ✓ **Double quality guarantee** from both manufacturer side and ACC side after production and before delivery.
- ✓ Approved by many authorized institutions from different fields such as **NSF, BV, HALA, Kosher**.etc.

This series activated carbon for VOCs treatment, with large working capacity, good desorption performance, small gas flow resistance, light specific gravity and other characteristic. It has excellent adsorption for hydrocarbon, also widely used in other industrials such as chemical, oil, petrochemical, electronics, plastic, etc.

### SPECIFICATIONS

Types	GP 68-1100 C	GP 68-950 C
CTC (%)	>90	>70
Benzene adsorption (%)	>40	>35
Iodine adsorption (mg/g)	1100	950
Surface area (m2/g)	1400-2400	1000-1300
Bulk density (g/ml)	0.33-0.38	0.33-0.38
Ignition temperature (°C)	400-450	400-450
Hardness (%)	70-90	70-90
Ash (%)	<6	5-8
Moisture (%)	<5	<5
Particle Size (mesh)	6 x 8	6 x 8

**Package:** Packed in 350kg bag.  
Other packaging is available upon your request.

**Standards:** All the above test methods are performed using ASTM protocol for activated carbon.